

4004.11-1

2

PATENT

Please amend the specification as follows:

In the Specification:

On page 5, in line 22 replace the paragraph as follows:

Figure 4 illustrates another embodiment of an implanted stimulator according to the invention.

On page 5, after line 29 insert the following new paragraph:

Figure 4C is an enlarged portion of Figure 4B as indicated in Figure 4B.

On page 19, replace the paragraph beginning on line 23 as follows:

Referring to Figures 4, and 4A-4[[B]]C, an alternative embodiment of the invention is illustrated. A stimulator 90 comprises a fixation device 93 including an electronics housing 94 with electrodes 91, 92 and electronic circuitry 125 coupled to the electrodes 91, 92. The electronic circuitry 125 is powered by battery 144 contained in a removable battery housing 95 that is configured to be removably coupled to the fixation device 93 in electrical communication with the electronics unit 125 contained in the electronics housing 94. In particular, the battery housing 95 includes magnets 98, 99 that may be coupled with magnets 104, 105 on the inner wall 106 of the electronics housing 94. Electrical contacts 96, 97 on the battery housing 95 align with electrical contacts 102, 103 on the inner wall 106 of the electronics housing 94 when the magnets 98, 99 are correspondingly aligned with magnets 104, 105 on the electronics housing 94. When the magnets 98, 99 are

BEST AVAILABLE COPY

4004.11-1

3

PATENT

aligned with magnets 104, 105 and the battery housing is coupled to the electronics housing 94, contacts 96, 97 are correspondingly electrically coupled to contacts 102, 103 so that the battery 144 provides power to the electronic circuitry 125 among other things, to deliver stimulating pulses to the duodenum 24 as described herein with reference to Figures 5 and 6. As shown in Figure 4C, contact 96 comprises a protruding portion 107 that is positioned in recess 108 in inner wall 106 in electronics housing 94. Contact 102 engages protruding member 107 so that electrical contact is made with contact 96. O-ring 109 seals electrical contacts within recess 108.

BEST AVAILABLE COPY